

เครื่องขัดแบบถึงถึง แบบช้า & แบบเร็ว (LOW SPEED & HIGH SPEED BARREL)



Feature:

1. Posses of frequency converter, time controller, ensuring operation process steady and uniform finishing quality.
2. High efficiency discharging door, easy to operate.
3. Optional double barrel, designed for large quantity or different lots.
4. Convenient to operate, can continuously work for 24 hours.

MODEL	Capacity	L x W x H (mm)	Motor (kw)	Weight (kg)	Speed (rpm)	Lining Thickness (mm)
WGP25	25	680 x 700 x 750	0.55	100	85	8
WGP50	50	730 x 720 x 1200	1.1	150	60	8
WGP100	100	1020 x 900 x 1300	1.1	200	40	10
WGP200	200	1090 x 1000 x 1420	2.2	500	30	10
WGP300	300	1450 x 1000 x 1420	2.2	560	30	10
WGP500	500	1660 x 1300 x 1520	5.5	1000	25	10



MODEL	Capacity	L x W x H (mm)	Motor (kw)	Speed (rpm)	Lining Thickness (mm)
WGP140 x 2	140 x 2	2570 x 850 x 1267	3.0	40	10
WGP300 x 2	300 x 2	3000 x 1300 x 1450	4.0	30	10
WGP500 x 2	500 x 2	3870 x 1150 x 1420	7.5	25	10