

Brown & White Aluminium Oxide



This sharp angular abrasive is the second hardest mineral after diamond. It is fast cutting and does not contain free silica. It give a matt finish, or produces anchor or 'tooth' patterns on most metal surface and can be used economically in closed system environment. APPLICATION The range of application is limitless - the removal of sand from casting; surface preparation prior to enameling, plating or bonding; etching; descaling, deburring, cleaning moulds, glass carving and decorative works in glass industry.

Typical		
Physicla & Chemical	Brown	White
Properties	AL203	AL203
Colour	Dark brown	White
Physical Nature	Hard & very tough	Hard & fible
Particle Specific Gravity	3.88	3.9
Melting Point	2000°C	2050°C
Hardness MOH'S Scale	9.0	9.0

Aluminium Oxide

Typical Chemicle Analysis	Brown	White
AL ₂ O ₃	≥ 95.00 (#4-80) ≥ 94.00 (#90-150) ≥ 93.00 (#180-220)	≥ 98.50 (#12-150) ≥ 98.20 (#180-220) ≥ 98.00 (#240-600)
SiO ₂	≤ 0.70	≤ 0.15
FE ₂ O ₃	≤ 0.30	≤ 0.10
TiO ₂	≤ 3.00	-
CaO	≤ 0.60	≤ 0.10
Na ₂ O	-	≤ 0.35
Cr ₂ O ₃	-	-
ZrO ₂ + HFO ₂	-	-

Standard Packing: 25kg /
poly-woven bag. Paper
bag is available. Wooden
pallet packing or jumbo
bag packing is available.

Specifications	
Grade	Micro Size
Mesh 8	2360
Mesh 10	2000
Mesh 12	1700
Mesh 14	1400
Mesh 16	1180
Mesh 20	850
Mesh 24	740
Mesh 30	600
Mesh 36	480
Mesh 40	425
Mesh 46	326
Mesh 60	250
Mesh 80	180
Mesh 90	166
Mesh 100	150
Mesh 120	125
Mesh 150	100
Mesh 180	83
Mesh 220	68

Other sizes are also available

21/62 หมู่ 3 ต.ลำโพ อ.บางบัวทอง จ.นนทบุรี 11110

21/62 Moo 3 Lampo, Bangbuathong, Nonthaburi, 11110

Tel : (+66) 2 194-4346-7 Fax : (+66) 2194-4348

E - Mail : sales@rpv.co.th

www.rpv.co.th